



CONSTRUCTION

1. The Box Series Concrete Planters are cast with a minimum wall thickness of 3 inches. Planters have an average strength tested at 28-30 days of 5,810 psi.
2. Planters are lightly sanded and sealed, inside and outside, to enhance color and protect surfaces from moisture, dirt, and stains.
3. Planters are manufactured with standard 1", 1.5", or 2" drain holes or no drain holes. Quantity and placement as directed by Purchaser .
4. Holes are cast into planter using standard PVC pipe trade sizes. Holes cannot be added after casting as doing so will void unit warranty.
5. Custom sizes are not available.

SURFACE FINISH

1. Planters will have a naturally pitted surface finish. (*Reference Manufacturer's Concrete Finish Sheet*)

CONCRETE COLOR SELECTION

1. Planters are offered in a standard gray (no pigment), or select integral color pigments. (*Reference Manufacturer's Concrete Finish Sheet*)
2. Premium colors are additional, including blues, greens, and graphite black.

BOX SERIES STANDARD SIZES

PRODUCT ID	LENGTH	WIDTH	HEIGHT	THICKNESS	AVG. WT.
BX_CON 202014	20"	20"	14"	3 IN.	385 lbs
BX_CON 242418	24"	24"	18"	3 IN.	580 lbs
BX_CON 303018	30"	30"	18"	3 IN.	770 lbs
BX_CON 481824	48"	18"	24"	3 IN.	1015 lbs
BX_CON 601824	60"	18"	24"	3 IN.	1214 lbs
BX_CON 721824	72"	18"	24"	3 IN.	1414 lbs
BX_CON 242424	24"	24"	24"	3 IN.	725 lbs
BX_CON 482424	48"	24"	24"	3 IN.	1160 lbs
BX_CON 404024	40"	40"	24"	3 IN.	1370 lbs
BX_CON 161630	16"	16"	30"	3 IN.	548 lbs
BX_CON 482430	48"	24"	30"	3 IN.	1378 lbs
BX_CON 602430	60"	24"	30"	3 IN.	1631 lbs
BX_CON 722430	72"	24"	30"	3 IN.	1885 lbs
BX_CON 303030	30"	30"	30"	3 IN.	1133 lbs