



CY\_40CON



CY\_26CON



CY\_22CON



CY\_18CON



CY\_15CON



CY\_15.2CON



## CONSTRUCTION

1. The Cypress Series Concrete Planters are cast with a minimum wall thickness of 3 inches. Planters have an average strength tested at 28-30 days of 5,810 psi.
2. Planters are lightly sanded and sealed, inside and outside, to enhance color and protect surfaces from moisture, dirt, and stains.
3. Planters are manufactured with standard 1", 1.5", or 2" drain holes or no drain holes. Quantity and placement as directed by Purchaser .
4. Holes are cast into planter using standard PVC pipe trade sizes. Holes cannot be added after casting as doing so will void unit warranty.
5. Custom sizes are not available.

## SURFACE FINISH

1. Planters will have a naturally pitted surface finish. (*Reference Manufacturer's Concrete Finish Sheet*)

## CONCRETE COLOR SELECTION

1. Planters are offered in a standard gray (no pigment), or select integral color pigments. (*Reference Manufacturer's Concrete Finish Sheet*)
2. Premium colors are additional, including blues, greens, and graphite black.

## CYPRESS SERIES CONCRETE STANDARD SIZES

| PRODUCT ID | TOP O.D. | HEIGHT | BASE O.D. | THICKNESS | AVG. WT. |
|------------|----------|--------|-----------|-----------|----------|
| CY_40CON   | 26"      | 40"    | 16"       | 3 IN.     | 680 lbs  |
| CY_26CON   | 36"      | 26"    | 18"       | 3 IN.     | 680 lbs  |
| CY_22CON   | 30"      | 22"    | 15"       | 3 IN.     | 472 lbs  |
| CY_18CON   | 42"      | 18"    | 26"       | 3 IN.     | 578 lbs  |
| CY_15CON   | 22"      | 15"    | 10"       | 3 IN.     | 175 lbs  |
| CY_15.2CON | 30"      | 15"    | 15"       | 3 IN.     | 365 lbs  |