



### CONSTRUCTION

1. The Frio Series Steel Powder Coated Planters are constructed of ASTM A1011 grade Carbon Steel. Planters are fabricated using a 12 ga. thickness.
2. Planters are coated with an exterior grade polyester powder coat finish, available in standard stock and non-standard stock RAL colors. Marine grade finish can be provided for an upcharge per unit.
3. Planters are manufactured with standard 1", 1.5", or 2" drain holes or no drain holes. Quantity and placement as directed by Purchaser. Holes are cut to nominal O.D. for standard PVC pipe trade sizes.

### STANDARD SELECTIONS

1. Standard lip = 2" wide lip with no return.
2. Standard toe-kick = 2" H x 2" inset.

### CUSTOMIZATION

1. Fabrication of F&F Steel Powder Coated Frio Series can be customized to designer specified sizes for DIAM. X H. Custom size units will be priced on labor, material, and thickness.
2. Flat base, no toe-kick.

### POWDER COAT FINISH

(Reference Form & Fiber Metal Finishes sheet)



### FRIO SERIES STEEL POWDER COATED STANDARD SIZES

PRODUCT ID	DIAMETER	HEIGHT	THICKNESS	AVG. WT.
FR_42S	26"	42"	12 ga.	120 lbs
FR_30S	30"	30"	12 ga.	112 lbs
FR_24S	36"	24"	12 ga.	144 lbs
FR_18S	60"	18"	12 ga.	201 lbs
FR_18.2S	28"	18"	12 ga.	72 lbs
FR_24.2S	24"	24"	12 ga.	83 lbs